

HEAVY STRETCH 260 FR

PROPERTIES	
Article number	F/936-FR-02
Textile application	Pop up system, Textile frame (SEG)
Available roll width	160 cm, 320 cm
Available roll length	50 m
Base material	100% polyester
Core	3"
Flame retardant	Yes – ask our customer service for certification
Reach	Yes
OEKO-TEX® Certified	Yes
Printing side	Inside
PVC free	Yes
Structure	Knitted
Sublimation settings	195°C – ± 45 seconds
Weight textile	260 gsm

USP's

• High opacity (no see-through)

EXO FABRICS

- 5-10% stretch
- Crease free
- Non fraying / cold cutting
- Flame Retardant





Notice: TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

.....

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications.

Texo Trade Services | Oostbaan 601 | 2841 ML Moordrecht | The Netherlands T +31 182 62 39 44 | E sales@texo-trade.com | W texo-trade.com

