

## WHITEBACK SOFT FR

### PROPERTIES

|                              |   |
|------------------------------|---|
| <b>Article number</b>        | F/955-FR-02   |
| <b>Textile application</b>   | Blockout, Lightbox, Roll up banner, Textile frame (SEG) |
| <b>Available roll width</b>  | 160 cm, 320 cm  |
| <b>Available roll length</b> | 50 m  |
| <b>Base material</b>         | 100% polyester  |
| <b>Core</b>                  | 3"  |
| <b>Flame retardant</b>       | Yes – ask our customer service for certification        |
| <b>Reach</b>                 | Yes   |
| <b>OEKO-TEX® Certified</b>   | Yes   |
| <b>Printing side</b>         | Inside  |
| <b>PVC free</b>              | Yes   |
| <b>Structure</b>             | Knitted with coating                                    |
| <b>Sublimation settings</b>  | 185°C – ± 45 seconds                                    |
| <b>Weight textile</b>        | 300 gsm   |

### USP's

- Dimout with white backside
- 3–5% stretch
- Matt finish
- Non fraying / cold cutting
- Soft hand
- Flame Retardant



**Notice:** TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications.

