

## TEXPRINT HR 105 G/M<sup>2</sup>

### PROPERTIES

<b>Article number</b>	SX30HR
<b>Available sheet size</b>	A4, A4+, A3, A3+
<b>Available roll width</b>	33 cm, 43 cm
<b>Available roll length</b>	34 m
<b>Core</b>	2"
<b>Dye sub coating type</b>	Semi-porous coating
<b>Drying properties</b>	High speed drying
<b>Printing side</b>	Outside
<b>Suitable for segment</b>	Metal, aluminium or ceramics, Textile, Textile non-porous
<b>Weight transfer paper</b>	105 gsm

### USP's

- Very fast drying
- Superb stability against wet cockling
- Semi-porous coating – reduces outgassing
- Available in DIN sheets sizes
- Available in rolls for Epson (<15 cm diameter)
- Suitable for metal and ceramics



**Notice:** TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications.