

## BASIC DISPLAY PREMIUM 220 FR

### PROPERTIES

<b>Article number</b>	F/165-FR-02
<b>Textile application</b>	Textile frame (SEG)
<b>Available roll width</b>	160 cm, 320 cm, 505 cm
<b>Available roll length</b>	100 m
<b>Base material</b>	100% polyester
<b>Core</b>	3"
<b>Flame retardant</b>	Yes – ask our customer service for certification
<b>Reach</b>	Yes
<b>OEKO-TEX® Certified</b>	Yes
<b>Printing side</b>	Inside
<b>PVC free</b>	Yes
<b>Structure</b>	Knitted
<b>Sublimation settings</b>	195°C – ± 45 seconds
<b>Weight textile</b>	220 gsm

### USP's

- 2-3% stretch
- Available up to 5 m width
- Crease free
- Matt finish
- No curling edges
- Non fraying / cold cutting
- Flame Retardant
- PVC free



**Notice:** TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications.

