TTS printable textiles & transfer printing media

TEXO FABRICS

NON WOVEN STITCH + AS 130

PROPERTIES	
Article number	F/401-XX-06
Textile application	Outdoor
Available roll width	160 cm, 320 cm
Available roll length	75 m
Base material	100% recycled polyester
Core	3"
Flame retardant	No
OEKO-TEX® Certified	Yes
Printing side	Inside
PVC free	Yes
Structure	Non-woven
Sublimation settings	185°C – ± 40 seconds
Weight textile	130 gsm

USP's

- Base fabric from recycled PET bottles
- PVC free
- Economic
- Matt finish
- Non fraying / cold cutting

COLD CUT | NON FR | LTX | PVC FREE | SUB PAPER TRANSFER | SUB DIRECT | USE INDOOR &OUTDOOR | UV





Notice: TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications.

Texo Trade Services | Oostbaan 601 | 2841 ML Moordrecht | The Netherlands
T +31 182 62 39 44 | **E** sales@texo-trade.com | **W** texo-trade.com