TTS
www.texo-trade.com

SOLAR

DISPLAY BLOCKOUT PRO FR

PROPERTIES

Article number	SL-BL03
Base material	100% polyester
Weight	350 gsm
Yarn dtex	330x330 dtex
Tensile strength	1900x1090 N/5cm
Tear strength	160x70 N
Opacity	100%
Available roll width	160 and 320 cm

USP's

- 100% PVC free
- complete blockout
- anti-curling
- printable on both sides
- good strength
- tight and smooth
- FR

UV LTX SOL FR COLD CUT USE INDOOR&OUTDOOR

Applications: hanging banner, roll up banner, pole banner, display

Notice: TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modications.

PVC FREE   PHTHALATE FREE   OEKO TEX®

Texo Trade Services BV | Oostbaan 601 | 2841 ML Moordrecht | The Netherlands
T +31 182 62 39 44 | E sales@texo-trade.com | W www.texo-trade.com